

# Vag 32v abz v8 turbo 33H240/33H220

- Hionta OEM-akseliin
- Alkuperäisille hydraulisille paininkupeille.

## INT

|                       |                         |                        |                        |
|-----------------------|-------------------------|------------------------|------------------------|
| Clearance cold        |                         | hydr                   |                        |
| Clearance hot         |                         |                        |                        |
| Duration              |                         | 255                    |                        |
| Duration 1 mm/1 mm    | 0-40                    | 220                    |                        |
| Max lift cam          |                         | 10.04mm                |                        |
| Real valve lift       |                         |                        |                        |
| Profile               |                         | 33H220                 |                        |
| Valves Split tdc      | after clearance setting | Int 1.0mm              | Ext 1.9mm              |
| Lobe angle separation |                         |                        |                        |
| Lobe centerline       |                         | In lobe centerline 110 | Ex lobe centerline 112 |

## EXT

|                    |      |         |  |
|--------------------|------|---------|--|
| Clearance cold     |      | hydr    |  |
| Clearance hot      |      |         |  |
| Duration           |      | 275     |  |
| Duration 1 mm/1 mm | 8-52 | 240     |  |
| Max lift cam       |      | 10.82mm |  |
| Real valve lift    |      |         |  |
| Profile            |      | 33H240  |  |